



Material
 Screw: M2.5,Steel, Zn plated
 Cage: Brass,Nickel plated
 Pin header: Brass , Tin plated
 Housing: PA66,UL94V-0

Electrical
 Rated voltage: 300V
 Rated current: 15A
 Wire range: 22~14AWG 1.5mm²
 Contact Resistance: 20mΩ
 Insulation resistance: 500MΩ/DC500V
 Withstand voltage: AC2000V/1min

Mechanical
 Temp. Range: -40℃~+105℃
 Soldering: 250℃±5℃for 5S
 Torque: 0.4Nm(3.54Lbin)
 Strip length: 6~7 mm

Order Information

RHTBY02-5.00-XXP-4 S XX
 Terminal Block
 Pitch
 No: of Pole
 Product Code:00~99
 Screw: S-Slot Screw
 C-Cross Screw
 Color: 4-Green

PCB LAYOUT

G	NINGBO RHT ELECTRONIC CO.,LTD	UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN	Screw CONN Terminal Block 5.00mm			
		0~3	3~18	18~50	50~120	CHK'D BY FENG	THIRD ANGLE PROJECTION	RHTBY02-5.00-XXP-4S	
		±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN			