



Electrical :

Rated voltage: 300V
 Rated current: 16A
 Contact resistance: 20m Ω
 Insulation resistance: 5000M Ω /1000V
 Withstanding Voltage: AC15000V/1Min
 Wire range: 22-14AWG 2.5mm²

Material:

Screws: M3 steel Zinc plated
 Wire guard: phosphor bronze Ni plated or stainless steel
 Pin header: Brass, Tin plated
 Housing: PBT,UL94V-0

Mechanical:

Temp. Range: -30°C~+120°C
 MAX Soldering:+250°C for 5 Sec.
 Torque: 0.5Nm (4.5lb.in)
 Strip length: 4.5-5mm

Ordering Information

Product NO: RHTBY60-7.50-03P-3S

Series No. _____ S=Slot Screw
 Pitch 7.50=7.50mm _____ Color: 2=Blue, 3=Black
 _____ Pin Number:02/03 Pin

RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4			SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG	THIRD ANGLE PROJECTION
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	

Screw Conn Term Block 7.50mm

RHTBY60-7.50-03P-3S