

Material
 Housing:PA66, UL94V-0
 Cage:Brass,Ni plated
 Clamp:Phosphor bronze, Ni plated
 Screws:M2.0, Steel,Zn plated

Electrical
 Rated voltage:300V
 Rated current:8A
 Contact Resistance:20mΩ
 Insulation resistance:500MΩ/DC500V
 Withstand voltage:AC2000V/1min
 Wire Range:28~14AWG1.0mm²

Mechanical
 Temp. Range:-40℃+105℃
 Strip length:6~7mm
 Torque:0.2Nm(1.7Lbin)

Order Information


RHTBYDKFF-5.08-XXP-4 S 00
 Terminal Block
 Pitch
 No. of Pole
 Color:4-Green
 Screw:S-Slot Screw C-Cross Screw
 Product Code: 00~99



NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4				SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG	THIRD ANGLE PROJECTION	
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	RHTBYDKFF-5.08-XXP-4S-00	

Pluggable Terminal Block 5.08 MM



RHTBYDKFF-5.08-XXP-4S-00