





RoHS Compliance



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)



Material:
Standard:PBT/PA6T
Contact:Brass
Plating:Au Or Sn Over Ni
Insulator:Polyester,UL94V-0

Electrical Characteristics:
Rated Current:1.5AMP
Contact Resistance:20mΩ Max
Withstand Voltage:500V AC/DC
Insulator Resistance:1000MΩ Min

Mechanical
Operating Temperature:-40℃~+105℃
Max.Processing Temp:230℃ For 30-60
Seconds (260℃ For 10 Seconds)

Order Information:
RHTAY08B-4.3-1-XX-S-B



Female Header
Series 08B:2.00mm
Plastics Height:4.3mm
Per Row:Single Layer
Pin: No.of Pins (1x40)
Type: Straight Pin
Material:A=PBT B=PA6T C=LCP

RHTECP NINGBO RHT ELECTRONIC CO.,LTD



UNITS:mm	SHEET SIZE: A4		SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN

2.0x4.3mm Female Header
Single Layer, Straight Pin, 1xN Pin
THIRD ANGLE PROJECTION
 RHTAY08B-4.3-1-XX-S-B

RoHS Compliance



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)



Material:
Standard:PBT/PA6T
Contact:Brass
Plating:Au Or Sn Over Ni
Insulator:Polyester,UL94V-0

Electrical Characteristics:
Rated Current:1.5AMP
Contact Resistance:20mΩ Max
Withstand Voltage:500V AC/DC
Insulator Resistance:1000MΩ Min

Mechanical
Operating Temperature:-40℃~+105℃
Max.Processing Temp:230℃ For 30-60
Seconds (260℃ For 10 Seconds)

Order Information:
RHTAY08B-4.3-2-XX-S-B



Female Header
Series 08B:2.00mm
Plastics Height:4.3mm
Per Row:Double Layer
Pin:No. Of Pins(02~80)
Type:Straight Pin
Material:A=PBT B=PA6T C=LCP

RHTECP NINGBO RHT ELECTRONIC CO.,LTD


UNITS:mm	SHEET SIZE: A4			SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG	
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	

2.0x4.3mm Female Header
Double Layer, Straight Pin, 2xN Pin
THIRD ANGLE PROJECTION
 RHTAY08B-4.3-2-XX-S-B

RoHS Compliance



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)



Material:
Standard:PBT/PA6T
Contact:Brass
Plating:Au Or Sn Over Ni
Insulator:Polyester,UL94V-0

Electrical Characteristics:
Rated Current: 1.5AMP
Contact Resistance:20mΩ Max
Withstand Voltage:500V AC/DC
Insulator Resistance:1000MΩ Min

Mechanical
Operating Temperature:-40°C~+105°C
Max.Processing Temp:230°C For 30-60
Seconds (260°C For 10 Seconds)



Order Information:
RHTAY08B-4.3-1-XX-R1-B
Female Header
Series 08B:2.00mm
Plastics Height:4.3mm
Per Row:Single Layer
Pin: No.of Pins (1x40)
Right Angle Pin:R1 Type
Material:A=PBT B=PA6T C=LCP

RHTECP NINGBO RHT ELECTRONIC CO.,LTD


UNITS:mm	SHEET SIZE: A4			SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG	
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	

2.0x4.3mm Female Header Single Layer,Right Angle Pin, 1xN Pin	
THIRD ANGLE PROJECTION 	RHTAY08B-4.3-1-XX-R1-B

RoHS Compliance



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)



Material:
Standard:PBT/PA6T
Contact:Brass
Plating:Au Or Sn Over Ni
Insulator:Polyester,UL94V-0

Electrical Characteristics:
Rated Current:1.5AMP
Contact Resistance: 20mΩ Max
Withstand Voltage:500V AC/DC
Insulator Resistance:1000MΩ Min

Mechanical
Operating Temperature:-40℃~+105℃
Max.Processing Temp:230℃ For 30-60
Seconds (260℃ For 10 Seconds)

Order Information:
RHTAY08B-4.3-1-XX-R2-B



Female Header
Series 08B:2.00mm
Plastics Height:4.3mm
Per Row:Single Layer
Pin: No.of Pins (1x40)
Right Angle Pin:R2 Type
Material:A=PBT B=PA6T C=LCP

RHTECP NINGBO RHT ELECTRONIC CO.,LTD



UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5
			CHK'D BY FENG
			APPR BY ZHAN

2.0x4.3mm Female Header Single Layer,Right Angle Pin, 1xN Pin	
THIRD ANGLE PROJECTION 	RHTAY08B-4.3-1-XX-R2-B

RoHS Compliance



Recommended P.C.B Layout (Top Side)
(PCB BOARD TOLERANCE ±0.05)



Material:
Standard: PBT/PA6T
Contact: Brass
Plating: Au or Sn Over Ni
Insulator: Polyester, UL94V-0

Electrical Characteristics:
Rated Current: 1.5AMP
Contact Resistance: 20mΩ Max
Withstand Voltage: 500V AC/DC
Insulator Resistance: 1000MΩ Min


Mechanical
Operating Temperature: -40°C ~ +105°C
Max. Processing Temp: 230°C For 30-60
Seconds (260°C For 10 Seconds)

Order Information:
RHTAY08B-4.3-2-XX-R-B



Female Header
Series 08B: 2.00mm
Plastics Height: 4.3mm
Per Row: Double Layer
Pin: No. of Pins (02~80)
Type: Right Angle Pin
Material: A=PBT B=PA6T C=LCP

 NINGBO RHT ELECTRONIC CO.,LTD



UNITS:mm	SHEET SIZE: A4		SCALE: ---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN

2.0x4.3mm Female Header
Double Layer, Right Angle Pin, 2xN Pin
THIRD ANGLE PROJECTION
 RHTAY08B-4.3-2-XX-R-B

RoHS Compliance



Recommended P.C.B Layout (Top Side)
(PCB BOARD TOLERANCE±0.05)



Dimension Antitheses List (mm)

ITEM	L1	L2	Plastic Height
Standard	3.50	2.00	4.30
Nonstandard	---	---	---

Material:

Standard:PBT/PA6T

Contact:Phosphor Bronze

Plating:Au Or Sn Over Ni

Insulator:Polyester,UL94V-0

Electrical Characteristics:

Rated Current:1.5AMP

Contact Resistance:20mΩ Max

Withstand Voltage:500V AC/DC

Insulator Resistance:1000MΩ Min

Mechanical

Operating Temperature:-40℃~+105℃

Max.Processing Temp:230℃ For 30-60

Seconds (260℃ For 10 Seconds)

Order Information:

RHTAY08B-4.3-1-XX-RM-L1xL2-N-B-R

Female Header

Series 08B:2.00mm

Plastics Height:4.3mm

Per Row:Single Layer

Pin:No. Of Pins(1x40)

SMT Type:Horizontal SMT

Size:L1xL2

Post:W=With Post N=W/O Post

Material:A=PBT B=PA6T C=LCP

Packing:

A=Tray T=Tube M=Reel+Mylar

P=Tube+Cap R=Reel+Cap



RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5



CHK'D BY FENG
APPR BY ZHAN

2.0x4.3mm Female Header Single Layer,Horizontal SMT, 1xN Pin	
THIRD ANGLE PROJECTION 	RHTAY08B-4.3-1-XX-RM-L1xL2-N-B-R

RoHS Compliance



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)



Dimension Antitheses List (mm)			
ITEM	L1	L2	Plastic Height
Standard	3.00	2.00	4.30
Nonstandard	---	---	---

Material:
Standard:PBT/PA6T
Contact:Brass
Plating: Au or Sn Over Ni
Insulator: Polyester, UL94V-0

Electrical Characteristics:
Rated Current: 1.5AMP
Contact Resistance: 20mΩ Max
Withstand Voltage: 500V AC/DC
Insulator Resistance: 1000MΩ Min

Mechanical
Operating Temperature: -40°C~+105°C
Max. Processing Temp: 230°C For 30-60
Seconds (260°C For 10 Seconds)

Order Information:
RHTAY08B-4.3-1-XX-W-L1xL2-B
Female Header
Series 08B: 2.00mm
Plastics Height: 4.3mm
Per Row: Single Layer
Pin: No. of Pins (1x40)
Type: Bottom Entry
Size: L1xL2
Material: A=PBT B=PA6T C=LCP



NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5



CHK'D BY FENG
APPR BY ZHAN

2.0x4.3mm Female Header
Single Layer, Bottom Entry, 1xN Pin
THIRD ANGLE PROJECTION
 RHTAY08B-4.3-1-XX-W-L1xL2-B

RoHS Compliance



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)



Dimension Antitheses List (mm)			
ITEM	L1	L2	Plastic Height
Standard	3.00	6.00	4.30
Nonstandard	---	---	---

Material:
Standard:PBT/PA6T
Contact:Brass
Plating:Au Or Sn Over Ni
Insulator:Polyester,UL94V-0

Electrical Characteristics:
Rated Current:1.5AMP
Contact Resistance:20mΩ Max
Withstand Voltage:500V AC/DC
Insulator Resistance:1000MΩ Min

Mechanical
Operating Temperature:-40℃~+105℃
Max.Processing Temp:230℃ For 30-60
Seconds (260℃ For 10 Seconds)

Order Information:
RHTAY08B-4.3-2-XX-W-L1xL2-B
Female Header
Series 08B:2.00mm
Plastics Height:4.3mm
Per Row:Double Layer
Pin:No. Of Pins(02~80)
Type:Bottom Entry
Size:L1xL2
Material:A=PBT B=PA6T C=LCP

NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5

CHK'D BY FENG
APPR BY ZHAN

2.0x4.3mm Female Header
Double Layer,Bottom Entry,2xN Pin
THIRD ANGLE PROJECTION
 RHTAY08B-4.3-2-XX-W-L1xL2-B

RoHS Compliance

Material:

Standard:PBT/PA6T

Contact:Phosphor Bronze

Plating:Au Or Sn Over Ni

Insulator:Polyester,UL94V-0

Electrical Characteristics:

Rated Current:1.5AMP

Contact Resistance:20mΩ Max

Withstand Voltage:500V AC/DC

Insulator Resistance:1000MΩ Min

Mechanical

Operating Temperature:-40℃~+105℃

Max.Processing Temp:230℃ For 30-60

Seconds (260℃ For 10 Seconds)

Order Information:

RHTAY08B-4.3-1-XX-N-L1xL2-N-B-R

Pin Header Series

08B:2.00mm

Plastics Height:4.3mm

Per Row Single Layer

Pin:No. Of Pins(1x40)

SMT Pin:T1 Type,T2 Type

Size:L1xL2


Post:W=With Post N=W/0 Post

Material:A=PBT B=PA6T C=LCP



Packing:

A=Tray T=Tube M=Reel+Mylar


P=Tube+Cap R=Reel+Cap





T2 Type



T1 Type



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)



Dimension Antitheses List (mm)

ITEM	L1	L2	Plastic Height
Standard	4.60	4.50	4.30
Nonstandard	---	---	---

NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5

CHK'D BY FENG	APPR BY ZHAN
---------------	--------------

2.0mm Female Header Single Layer,SMT Pin, 1xN Pin	
THIRD ANGLE PROJECTION 	RHTAY08B-4.3-1-XX-N-L1xL2-N-B-R

RoHS Compliance

Material:

Standard:PBT/PA6T

Contact:Phosphor Bronze

Plating:Au Or Sn Over Ni

Insulator:Polyester,UL94V-0

Electrical Characteristics:

Rated Current:1.5AMP

Contact Resistance:20mΩ Max

Withstand Voltage:500V AC/DC

Insulator Resistance:1000MΩ Min

Mechanical

Operating Temperature:-40℃~+105℃

Max.Processing Temp:230℃ For 30-60

Seconds (260℃ For 10 Seconds)

Order Information:

RHTAY08B-4.3-2-XX-T-L1xL2-B-R

Pin Header Series

08B:2.00mm

Plastics Height:4.3mm

Per Row: Double Layer

Pin:No. Of Pins(02~80)

SMT:T=Without Post T3=With Post

Size:L1xL2





Material:A=PBT B=PA6T C=LCP

Packing:


A=Tray T=Tube M=Reel+Mylar

P=Tube+Cap R=Reel+Cap

Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)




T3=With Post



T=Without Post

Dimension Antitheses List (mm)

ITEM	L1	L2	Plastic Height
Standard	4.60	6.20	4.30
Nonstandard	---	---	---



RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5

CHK'D BY FENG	APPR BY ZHAN
---------------	--------------

2.0mm Female Header Double Layer,SMT Pin, 2xN Pin	
THIRD ANGLE PROJECTION	RHTAY08B-4.3-2-XX-T-L1xL2-B-R