



PCB Layout

Material:  
 Housing:PBT+Glass FilledPolyester  
 Flammability Rating : UL 94 V-0  
 Contacts: Phosphor Bronze  
 Plating:Gold Plating

Electrical:  
 Voltage Rating:125VAC  
 Current Rating:1.5A  
 Contact Resistance:30mΩ Max.  
 Insulation Resistance: 500MΩ Min.  
 Dielectric Strength:1000VAC Rms50Hz, 1 Min.  
 Durability:600 cycles Min.  
 Operation Temperature:-40℃+70℃

Order Information

RHTLY19-8P8C-XX

Contacts:8P8C  
 Plating Code:  
 01-1u" Gold Plating  
 02-3u" Gold Plating  
 03-6u" Gold Plating  
 04-15u" Gold Plating  
 05-30u" Gold Plating

**RHTECP** NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4			SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG	
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	

RJ45-8P8C Modular jacks,with HALF Shield

THIRD ANGLE PROJECTION



RHTLY19-8P8C-XX