



Material:  
 Housing: PBT+Glass Filled Polyester  
 Flammability Rating: UL94V-0  
 Contacts: Phosphor Bronze Ø0.46mm  
 Plating: Gold Plating  
 Electrical:  
 Voltage Rating: 125VAC  
 Current Rating: 1.5A  
 Contact Resistance: 30mΩ Max.  
 Insulation Resistance: 500MΩ Min.  
 Dielectric Strength: 1000V/AL Rms50Hz, 1 Min.  
 Durability: 600 cycles Min.  
 Operation Temperature: -40°C~+70°C

Order Information

RHTLY17-6P6C - X- 1 -XX

Contacts: 6P6C  
 Panel: W-With Panel  
 W/O-Without Panel  
 Color Code:  
 1-Block

Plating Code:  
 01-Fu" Gold Plating  
 02-3u" Gold Plating  
 03-6u" Gold Plating  
 04-15u" Gold Plating  
 05-30u" Gold Plating

NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4			SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG	
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	

THIRD ANGLE PROJECTION



RJ12-6P6C Modular Jacks

RHTLY17-6P6C-X-1-XX