




SECTION A-A



With Panel



Without Panel



PCB Layout

Material:
 Housing: PBT+Glass Filled Polyester
 Flammability Rating: UL94V-0
 Contacts: Phosphor Bronze
 Plating: Gold Plating
 Electrical:
 Voltage Rating: 125VAC
 Current Rating: 1.5A
 Contact Resistance: 30mΩ Max.
 Insulation Resistance: 500MΩ Min.
 Dielectric Strength: 1000VAL Rms50Hz, 1 Min.
 Durability: 600 cycles Min.
 Operation Temperature: -40°C~+70°C

Order Information

RHTLY45-8P8C- W- 1 -XX

Contacts: 8P8C
 Panel: W-With Panel
 W/O-Without Panel
 Color Code:
 1-Block

Plating Code:
 01-Fu* Gold Plating
 02-3u* Gold Plating
 03-6u* Gold Plating
 04-15u* Gold Plating
 05-30u* Gold Plating

NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4		SCALE:---		DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG	THIRD ANGLE PROJECTION
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	

RJ45-8P8C Modular Jacks

RHTLY45-8P8C-X-X-XX