

Material:  
 Housing:Engineering Thermoplastic  
 Flammability Rating:UL94V-0  
 Contacts:Phosphor Bronze  
 Plating:Gold Plating Over Nickel in Contact.  
 Tin Plating Over Nickel in Solder Area.

Electrical:  
 Voltage Rating: 125VAC  
 Current Rating:1.5A  
 Contact Resistance:40mΩ Max.  
 Insulation Resistance:1000MΩ Min.@500VDC  
 Dielectric Strength:1000VAL Rms 60Hz,1 Min.  
 Durability:750 cycles Min.  
 Operation Temperature:-20° +75°L

#### Order Information

RHTLY52-8P8C- S- 1 -XX

Contacts:8P8C

Color Code:  
1-Block


Plating Code:  
 01-Fu\*Gold Plating  
 02-3u\*Gold Plating  
 03-6u\*Gold Plating  
 04-15u\*Gold Plating  
 05-30u\*Gold Plating

**RHTECP** NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4			SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG	
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	

RJ45-8P8C Vertical Modular jacks

THIRD ANGLE PROJECTION



RHTLY52-8P8C-S-1-XX