


 PAD AREA  
 RECOMMENDED PCB LAYOUT  
 TOP VIEW(TOLERANCE±0.05)



#### DETECT SWITCH

CARD INSERTING POSITION	CLOSE	CLOSE ○ SW1 ○ SW1
NO CARD	OPEN	OPEN ○ SW1 ○ SW1

Card Is Not Inserted;  
 Sw2 And Sw 1/GND Pin Is Open  
 Card Is Inserted;  
 Sw2 And Sw1/GND Pin Is Close

#### Material:

Housing:High Temperature  
 Thermoplastic,UL94V-0,Black  
 Terminal:Copper Alloy  
 Shell:Stainless Steel.


#### Electrical:

Current Rating: 1.0A  
 Rating Voltage:50V  
 Contact Resistance:100mΩ Max.  
 Insulation Resistance:1000MΩ Min./500V DC  
 Dielectric Withstanding Voltage:500V AC  
 Solder Ability:255°C+5°C,5+0.5S  
 Durability:5000 Cycles Min.  
 Operating Condition: Temperature-40°C~+85°C



NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5
			CHK'D BY FENG
			APPR BY ZHAN

Micro SIM CONN:PUSH/PUSH, 8Pin, H1.56mm, With CD Pin	
THIRD ANGLE PROJECTION 	RHTAYIM-094-H1.56-R