


SIM Pin Assignment	
PIN#	Name
C1	VCC
C2	RST
C3	CLK
C5	GND
C6	VPP
C7	I/O



Material:

Insulator: High Temperature Thermoplastic, UL94V-0
 Contact: Copper Alloy, Plated 50u" Ni Overall, PAD Au 1U
 Shell: SUS, Plated 30U/MIN

Electrical:


Current Rating: 0.5A Amperes
 Voltage Rating: 5V AC/DC
 Ambient Temperature Range: -40°C~+85°C
 Storage Temperature Range: -40°C~+85°C
 Ambient Humidity Range: 95% R.H.Max
 Contact Resistance: 100mΩ Max
 Insulation Resistance: 1000MΩ Min./500VDC
 Mating Cycles: 3000-8000 Min Insertions
 Peak Temperature: 260°C



NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5

CHK'D BY FENG
APPR BY ZHAN



Nano SIM CONN,PUSH/PUSH,
6Pin,H1.37mm,With CD Pin

RHTAYIM-066-(6+1)P-H1.37-R