


SIM Pin Assignment	
PIN#	Name
C1	VCC
C2	RST
C3	CLK
C4	Reserved
C5	GND
C6	VPP
C7	I/O
C8	Reserved



Material:
 Insulator: High-Temperature Plastic, UL94V-0, Black
 Terminal: Copper Alloy, T=0.15mm
 Shell: Stainless Steel, T=0.15mm
 Finish:
 Terminal: 50µm Min Nickel Underplated On Alloy, Gold Plating On Contact Area, Flash Gold On Solder Tail.
 Shell: 50µm Nickel Underplated On Alloy, Gold Flash on Solder Latch.
 Electrical:
 Current Rating: 0.5A
 Voltage Rating: 5.0 Vrms.
 Insulation Resistance: 500M Min. At DC 500V DC
 Withstanding Voltage: 250V AC rms For 1 Minute.
 Contact Resistance: 100M Max. At 10mA/20mV MAX
 Operating Temperature: -55°C TO +85°C
 Mating Cycles: 5000 Insertions



NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5

CHK'D BY FENG
 APPR BY ZHAN

SIM CARD CONN: PUSH PUSH,
 6P,H1.85mm,SMD with CD Pin
 THIRD ANGLE PROJECTION
 RHTAYIM-064A-(6+2)P-H1.85-R