


RECOMMENDED PCB LAYOUT



Material
Housing: High Temperature Thermoplastic,
UL94V-0 LCP, Black.
Contact: Copper Alloy C2680,
Shell: Copper Alloy C2680

Finish:
Contact: Plated Gold In Mating Area,
Tin On Solder Tolls.
Shell: Nickel Plating

Electrical:
Current Rating: 1.0A/Contact Terminal.
Voltage Rating: 30V DC
Contact Resistance: 50mΩ Max.
Dielectric Withstanding Voltage:
300 V AC AT Sea Level.
Insulation Resistance: 100MΩ Min.
Connector Mate And Unmated Force
Mate Force: 3.0kgf Max.
Unmated Force: 0.7kgf Min.
Terminal Retention: 0.5kgf Min

Order Information

RHTAY29-5FA-B

Model

Serial Number


Color: B=Black

NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4		SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN

CONN MINI USB RCPT TYPE B R/A

THIRD ANGLE PROJECTION



RHTAY29-5FA-B