


Material
 Housing:High Temperature Thermoplastic,
 UL94V-0 LCP,Black.
 Contact:Copper Alloy C2680,
 Shell:Copper Alloy C2680/SPCC

Finish:
 Contact:Plated Gold In Mating Area,
 Tin On Solder Tolls.
 Shell:Nickel Plating

Electrical:
 Current Rating:1.0A/Contact Terminal.
 Voltage Rating:30V DC
 Contact Resistance:50mΩ Max.
 Dielectric Withstanding Voltage:
 300 V AC AT Sea Level.
 Insulation Resistance: 100MΩ Min.
 Connector Mate And Unmated Force
 Mate Force:3.0kgf Max.
 Unmated Force:0.7kgf Min.
 Terminal Retention:0.5kgf Min

Order Information



R-TAPE On Reel T-Tube

G	NINGBO RHT ELECTRONIC CO.,LTD	UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN	CONN MINI USB RCPT TYPE B SMD,MID MOUNT			
		0~3	3~18	18~50	50~120	CHK'D BY FENG	THIRD ANGLE PROJECTION		
		±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	RHTAY29-5FE-B-X		