

4	J	394V RIGHT PIN	3	H65Y
3	J	394V LEFT PIN	3	H65Y
2	W	394V HOUSING	1	H65Y
1	CX	394V INSERT	1	PA66+30%GF
NO	CODE	P/N	QTY	MATERIAL

Material:
Housing: Termoplastic, UL94V-0
Contact: Copper Alloy
Shell: Copper Alloy
Pin Plated: Gold 3u" Over 50u" Nickel

Electrical Characteristics:
Voltage Current Rating: 15AMP,40V AC
Insulation Resistance: 500MΩ Min
Contact Resistance: 50mΩ Max
Dielectric Withstanding Voltage: 500V AC
Temperature Range: -20°C~+85°C

ORDER INFORMATION

Product NO.: RHTAY394-6FA-B

IEEE 394 TYPE


Color: W=WHITE B=BLACK

RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm SHEET SIZE: A4 SCALE: ---
0~3 3~18 18~50 50~120
±0.12 ±0.15 ±0.3 ±0.5

DRWN BY PAN
CHK'D BY FENG
APPR BY ZHAN

IEEE 394 6 Pin Receptacle DIP 90° Upright



RHTAY394-6FA-B