

| 5 | G | 394P.H Back Cover | 1 | Steel |
|----|------|-------------------|-----|--------------|
| 4 | W | 394P Shell | 1 | Copper Alloy |
| 3 | J | 394P PIN | 3 | Copper Alloy |
| 2 | J | 394P Foront PIN | 3 | Copper Alloy |
| 1 | X | 394P INSERT | 1 | PA66+30%GF |
| NO | CODE | P/N | QTY | MATERIAL |

Material:

Housing: Termoplastic, UL94V-0

Contact: Copper Alloy

Shell: Copper Alloy

Pin Plated: Gold 3u" Over 50u" Nickel

Electrical Characteristics:

Voltage Current Rating: 1.5AMP.40V AC

Insulation Resistance: 500MΩ Min

Contact Resistance: 50mΩ Max

Dielectric Withstanding Voltage: 500V AC

Temperature Range: -20°C~+85°C

ORDER INFORMATION

Product NO.: RHTAY394-6FC-B

IEEE 394 TYPE

Color: W=WHITE B=BLACK

 NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm

SHEET SIZE: A4

SCALE: ---

DRWN BY PAN

IEEE 394 6 Pin Receptacle DIP 90° Type

0~3

3~18

18~50

50~120

CHK'D BY FENG

THIRD ANGLE PROJECTION


±0.12

±0.15

±0.3

±0.5

APPR BY ZHAN



RHTAY394-6FC-B