

Material:

Housing: Polycarbonate, Transparent

UL94V-0 Or UL94V-2

Contacts: Brass, Gold Plating

Electrical:

Rated Current: 125V AC 1.5A@25°C

Contact Resistance: 20mΩ Max.

Insulation Resistance: 500MΩ Min. 100V DC/Min

Withstand Voltage: 1000VAC/1 Minute

No Breakdown

Mechanical:

Insertion Force: 30N Max

Withdrawal Force: 30N Max.

Durability: 750 Cycles Min.

Operation Temperature: -40°C ~ +85°C

Order Information

RHTLYJ11-4P4C-xx X X

Point No. _____

Gold Plating _____

01-1u" Gold Plating

02-3u" Gold Plating

03-6u" Gold Plating

15-15u" Gold Plating

30-30u" Gold Plating

50-50u" Gold Plating

BLADE Type: _____

Flammability: _____

Blank-UL94V-2 0-UL94V-0



Type A



Type D

BLADE Type

SECTION A-A

RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm

SHEET SIZE: A4

SCALE: ---

DRWN BY PAN

UTP CAT3 4P4C RJ11 Modular Plugs

0~3

3~18

18~50

50~120

CHK'D BY FENG

THIRD ANGLE PROJECTION


±0.12

±0.15

±0.3

±0.5

APPR BY ZHAN



RHTLYJ11-4PxC-xxxx