

PCB Layout

Material:

Housing: Engineering Thermoplastic
 Flammability Rating :UL94V-0
 Contacts: Phosphor Bronze
 Plating: Gold Plating Over Nickel In Contact
 Tin Plating Over Nickel In Solder Area.

Electrical:

Voltage Rating:125VAC
 Current Rating:1.5A
 Contact Resistance:40mΩ Max.
 Insulation Resistance: 1000MΩ Min.@500VDC
 Dielectric Strength:1000VAC Rms 60Hz, 1 Min.
 Durability:750 Cycles Min.
 Operation Temperature:-20℃~+75℃

Order Information

RHTLY52-4P4C-S-1-XX

Contacts:4P4C

Color Code: 1-Black

Plating Code:

01-Fu"Gold Plating 02-3u"Gold Plating

03-6u"Gold Plating 04-15u"Gold Plating

05-30u"Gold Plating

RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4			SCALE:---
0~3	3~18	18~50	50~120	
±0.12	±0.15	±0.3	±0.5	


DRWN BY PAN

CHK'D BY FENG

APPR BY ZHAN

RJ11-4P4C Vertical Modular Jacks

THIRD ANGLE PROJECTION



RHTLY52-4P4C-S-1-XX