

PCB Layout

Material:

Housing:PBT+Glass Filled Polyester
 Flammability Rating:UL94V-0
 Contacts: Phosphor Bronze ∅0.46mm
 Plating:Gold Plating

Electrical:

Voltage Rating:125VAC
 Current Rating:1.5A
 Contact Resistance:30mΩ Max.
 Insulation Resistance: 500MΩ Min.
 Dielectric Strength:1000VAC Rms 50Hz,1 Min.
 Durability:600 cycles Min.
 Operation Temperature:-40℃~+70℃

Order Information


RHTLY57-8P8C-1-XX

Contacts:8P8C
 Color Code:1-Black
 Plating Code:
 01-Fu' Gold Plating
 02-3u' Gold Plating
 03-6u' Gold Plating
 04-15u' Gold Plating
 05-30u' Gold Plating

NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4				SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG	THIRD ANGLE PROJECTION	
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	RHTLY57-8P8C-1-XX	

Modular Jacks,RJ45-8P8C
 Jack Without SHELL,Black



RHTLY57-8P8C-1-XX