

Technical Parameters:

Rated Voltage:DC 30V

Rated Current: 0.5 A

Contact Resistance:0.03Ω,Max

Insulation Resistance:100MΩ,Min

Pressure:AC500V(50Hz)/1minute

Insertion Force:2~20 N

Life: 50000 Times

Operating Temperature:-30℃~70℃

Material:

Housing Material:PBT


Center Pin Material:

Terminal1:Brass

Terminal2:Copper Alloy

Terminal3:Brass

Bushing :Brass



Ø3.5 MATE PLUG

MODEL NO	001A	001AA	001AB
D DIA	With NUT M6X0.5	With NUT M6X0.5	With NUT M6X0.5
A	4.0mm	4.5mm	3.0mm
SCHEMATIC			

ORDER INFORMATION

RHTAYG3.5-001A A

3.5mm Dip Mono Jack

A: With NUT

B: Without NUT


Schematic:See Annex

NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5
CHK'D BY FENG		APPR BY ZHAN	

3.5MM MONO MINIATURE JACK SOCKET ROHS

THIRD ANGLE PROJECTION



RHTAYG3.5-001A