

T:16 Dimensions Of PC Board Holes  
Tolerance:±0.05(Printed-top View)


**SPECIFICATION**

Rated Load:DC 30V 1.0A  
Contact Resistance:30mΩ, Max  
Insulation Resistance:100MΩ, Min  
Withstand Voltage:AC500V  
Actuating Force:3-20N  
Life:5000 Cycles  
Operating Temperature:-30°C-70°C

NO	Description	QTY	Material	Plating
1	Flat Piece	1	C2680 t=0.40	Ag-Plating
2	Spring	1	C5191 t=0.25	Ag-Plating
3	Curve Piece	1	C2680 t=0.40	Ag-Plating
4	PIN	1	H59(Copper Alloy)	Cu/Sn-Plating
5	Housing	1	PA66	Black
6	Cover	1	PF	UL-94V0

PIN	∅2.0	∅2.5
APPD		

**SCHEMATIC**



NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4			SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG	
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	

DC POWER Jack DIP

THIRD ANGLE PROJECTION

RHTAYC-006