


T:16 Dimensions Of PC Board Holes
Tolerance:±0.1(Printed-top View)
Unless Otherwise Specified,
Tolerance On Decimal:±0.3

NO	Description	QTY	Material	Plating
1	Flat Piece	1	H62 Brass	MB:Cu Cu/Sn Plating
2	Curve Piece	1	Phosphor Bronze	MB:Cu Cu/Sn Plating
3	Spring	1	Phosphor Bronze	MB:Cu Cu/Sn Plating
4	PIN	1	H59 Brass	MB:Cu Ni Plating
5	Axis Support	1	H59 Brass	MB:Cu Ni Plating
6	Housing	1	PA66	---
7	Nut	1	H59(Copper Alloy)	MB:Cu Ni Plating
8	Washer	1	H59(Copper Alloy)	MB:Cu Ni Plating

PIN	∅2.0	∅2.5
APPD		

SCHEMA TIC



SPECIFICATION

Rated Load:DC 30V 0.5A
Contact Resistance:30mΩ, Max
Insulation Resistance:100MΩ, Min
Withstand Voltage:AC500V
Actuating Force:3-20N
Life:5000 Cycles
Operating Temperature:-30°C-70°C

RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4		SCALE:---	
0~3	3~18	18~50	50~120	
±0.12	±0.15	±0.3	±0.5	

DRWN BY PAN

CHK'D BY FENG

APPR BY ZHAN

DC POWER Jack DIP

THIRD ANGLE PROJECTION



RHTAYC-025A