



Technical Parameters:  
 Rated Voltage:DC 30V  
 Rated Current: 0.5 A  
 Contact Resistance:0.03Ω,Max  
 Insulation Resistance:100MΩ,Min  
 Pressure:AC500V(50Hz)/1minute  
 Insertion Force:2-20 N  
 Life: 50000 Times  
 Operating Temperature:-30°C~70°C  
 Material:

Terminal1:Copper Alloy  
 Terminal2:Copper Alloy  
 Terminal3:Copper Alloy  
 Terminal4:Copper Alloy  
 Terminal10: Brass  
 Terminal11: Brass  
 Housing:PA6T

ORDER INFORMATION

RHTAYPJ3.5-002A

3.5mm SMD Stereo Jack  
 Schematic:See Annex

MODEL NO	002	002A	002B	002C
SCHEMATIC				

**RHTECP** NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4		SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN

SMD Stereo Jack	
THIRD ANGLE PROJECTION	RHTAYPJ3.5-002