



PCB LAYOUT
(TOP VIEW)

MODEL NO	001A	001AA	001AB	001AC	001AD
SCHEMATIC					

Technical Parameters:
 Rated Voltage:DC 30V
 Rated Current: 0.5 A
 Contact Resistance:0.03Ω,Max
 Insulation Resistance:100MΩ,Min
 Pressure:AC500V(50Hz)/1minute
 Insertion Force:2-20 N
 Life: 50000 Times
 Operating Temperature:-30°C~70°C
 Material:

Terminal1:Copper Alloy
 Terminal2:Copper Alloy
 Terminal3:Copper Alloy
 Terminal 10: Brass
 Terminal 11: Brass
 Bushing: Brass
 Housing: PBT

ORDER INFORMATION

RHTAYSJ3.5-001A A

3.5mm Dip Stereo Jack
 Schematic:See Annex

NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5

CHK'D BY FENG
 APPR BY ZHAN

Dip Stereo Jack
 THIRD ANGLE PROJECTION

 RHTAYSJ3.5-001A