



| MODEL NO | 007A | 007AA |
|-----------|--------------------|--------------------|
| D DIA | With NUT M6X0.5 | With NUT M6X0.5 |
| A | 4.0mm | 4.0mm |
| SCHEMATIC | | |

Technical Parameters:

Rated Voltage:DC 30V

Rated Current: 0.5 A

Contact Resistance:0.03Ω,Max

Insulation Resistance:100MΩ,Min

Pressure:AC500V<50Hz>/1minute

Insertion Force:2-20 N

Life: 50000 Times

Operating Temperature:-30°C~70°C

Material:

Housing Material:PBT

Center Pin Material:

Terminal 1 :Brass

Terminal 2 :Copper Alloy

Terminal 3 :Brass

Bushing:Brass

ORDER INFORMATION

RHTAYSJ3.5-007A A

3.5mm Dip Stereo Jack

A: With NUT

B:Without NUT

Schematic:See Annex

RHTECP NINGBO RHT ELECTRONIC CO.,LTD

| | | | | |
|----------|----------------|-------|-----------|---------------|
| UNITS:mm | SHEET SIZE: A4 | | SCALE:--- | DRWN BY PAN |
| 0~3 | 3~18 | 18~50 | 50~120 | CHK'D BY FENG |
| ±0.12 | ±0.15 | ±0.3 | ±0.5 | APPR BY ZHAN |

Dip Stereo Jack

THIRD ANGLE PROJECTION

RHTAYSJ3.5-007A