



With NUT	M6X0.5	MODEL NO	008CA	008CAA	008CAB	008CAC	008CAD
D DIA		SCHEMATIC					

Technical Parameters:  
 Rated Voltage: DC 30V  
 Rated Current: 0.5 A  
 Contact Resistance: 0.03Ω, Max  
 Insulation Resistance: 100MΩ, Min  
 Pressure: AC 500V (50Hz) / 1 minute  
 Insertion Force: 2-20 N  
 Life: 50000 Times  
 Operating Temperature: -30°C ~ 70°C  
 Material:  
 Housing Cover: PBT  
 Center Pin Material:  
 Spring: Stainless Steel  
 Terminal 1, 2, 3, 10, 11: Brass  
 Bushing: Brass

ORDER INFORMATION

RHTAYSJ3.5-008CA A

3.5mm Dip Stereo Jack

A: With NUT

B: Without NUT

Schematic: See Annex

**RHTECP** NINGBO RHT ELECTRONIC CO., LTD

UNITS: mm	SHEET SIZE: A4		SCALE: ---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN

Dip Stereo Jack	
THIRD ANGLE PROJECTION	RHTAYSJ3.5-008CA