



With NUT M6X0.5	MODEL NO	008EA	008EAA	008EAB	008EAC	008EAD
D DIA	SCHEMATIC					

Technical Parameters:  
 Rated Voltage:DC 30V  
 Rated Current: 0.5 A  
 Contact Resistance:0.03Ω,Max  
 Insulation Resistance:100MΩ,Min  
 Pressure:AC500V(50Hz)/1minute  
 Insertion Force:2-20 N  
 Life: 50000 Times  
 Operating Temperature:-30°C~70°C  
 Material:  
 Housing Cover : PBT  
 Center Pin Material:  
 Spring: Stainless Steel  
 Terminal1,2,3,10,11 : Brass  
 Bushing: Brass

ORDER INFORMATION  
 RHTAYSJ3.5-008EA A

3.5mm Dip Stereo Jack  
 A:With NUT  
 B:Without NUT  
 Schematic:See Annex

**RHTECP** NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5
			CHK'D BY FENG
			APPR BY ZHAN

Dip Stereo Jack	
THIRD ANGLE PROJECTION	RHTAYSJ3.5-008EA