



Material:

- 1. Insulator: PBT, UL94V-0
- 2. Cover: PBT
- 3. Bao Yuan: Brass With H62 Y1=0.25mm, D, Cu/Sn
- 4. Left Short Pin: Brass With H62 Y1=0.25mm, D, Cu/Sn
- 5. Left Long Pin: Brass With H62 Y1=0.25mm, D, Cu/Sn
- 6. Right Long Pin: Brass With H62 Y1=0.25mm, D, Cu/Sn
- 7. Right short pin: Brass with H62 Y1=0.25mm, D, Cu/Sn

Electrical Characteristics.

- 1. Conditions Of Use
Ambient Temperature: -25°C~+70°C Relative Humidity: 95%(<40°C)
- 2. Contact Current Rating: 2A 12V DC
- 3. Contact Resistance: 30mΩ MAX
- 4. Insulation Resistance: 100MΩ Min
- 5. Dielectric Withstanding: 250V AC (50Hz) 1 min.
- 6. Insertion And Extraction Force: 5-35N
- 7. Life: 5000 Cycles

Order Information:

RHTAY85A-XX-B

85A: Without Shielded
 XX-No. of Pin
 03~08 pins
 B-Black G-Green

RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4			SCALE:---
0~3	3~18	18~50	50~120	
±0.12	±0.15	±0.3	±0.5	

DRWN BY PAN
 CHK'D BY FENG
 APPR BY ZHAN

Mini Din Jack
 THIRD ANGLE PROJECTION
 RHTAY85A-04-B

