



ARRANGEMENT OF CONTACTS			
NO. OF CONTACTS	3	4	5
PCB LAYOUT			
ARRANGEMENT OF CONTACTS			
NO. OF CONTACTS	6	7	8
PCB LAYOUT			

MATERIAL

Insulator: PBT UL94V-0 Or PPS
 Shell: Brass, Nickel/Tin Plated Or Tin Plated
 Contact: Phosphor Bronze, Gold/Tin plated
ENVIRONMENTAL
 Operating Temperature: -25°C~+70°C

ELECTRICAL

Contact Current Rating: 1 Amp 100VAC
 2 Amp 12VDC
 Dielectric Withstanding: AC 1000V/min.
 Insulation Resistance: 5000M OHM min AT 500V DC
 Contact Resistance: 30m ohm Max.
 Insertion Force: 4.5Kgf Max
 Withdrawal Force: 0.8Kgf Min
 Life: 5000 Cycles

ORDER INFORMATION

Product NO.: RHTAY85L-4 B

MINI DIN Jack Shell Series _____
 Pin Number _____
 3=3P 4=4P 5=5P
 6=6P 7=7P 8=8P
 Color : B=Black G=Green _____

NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4			SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG	
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	

MINI DIN Jack Shell Series
 THIRD ANGLE PROJECTION

 RHTAY85L