





Switching Characteristics:  
 Mechanical Life: 2000 Operations Per Switch  
 Operation Force: ≤9.8N Max.  
 Stroke: 2.0mm  
 Operation Temp: -20°C~+70°C  
 Electrical Life: 2000 Operations Per Switch-24 VDC 25mA  
 Contact Resistance: 50m Max. At Initial  
 Non-Switching Rating: 100mA, 50VDC  
 Switching Rating: 25mA, 24VDC  
 Circuit: Single Pole Single Throw

Model No.	No.Pos	A
RHTGYAR-01	1	4.10
RHTGYAR-02	2	6.64
RHTGYAR-03	3	9.18
RHTGYAR-04	4	11.72
RHTGYAR-05	5	14.26
RHTGYAR-06	6	16.80
RHTGYAR-07	7	19.34
RHTGYAR-08	8	21.88
RHTGYAR-09	9	24.42
RHTGYAR-10	10	26.96
RHTGYAR-12	12	32.04



Order Information  
 RHTGYAR-XX-X-X-X  
 Recessed Type Dip Switch  
 Number Of Pos.: 01~12Pos.  
 Color: R=Red, B=Blue, N=Black  
 0: Non-Sealed 1: With Sealed  
 Packaging: 0=Tube 1=Tape



PCB Layout

Soldering And Cleaning Processes Keep All Switch Contacts In Their "OFF" Position For All Operations

**RHTECP** NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5
CHK'D BY FENG		APPR BY ZHAN	

SPST Standard Right Angle Type Recessed  
 THIRD ANGLE PROJECTION  
 RHTGYAR