

Material:
 Housing: PBT+Glass Filled Polyester
 Flammability Rating: UL94V-0
 Contacts: Phosphor Bronze Ø0.46mm
 Plating: Gold Plating

Electrical:
 Voltage Rating: 125VAC
 Current Rating: 1.5A
 Contact Resistance: 30mΩ Max.
 Insulation Resistance: 500MΩ Min.
 Dielectric Strength: 1000VAC Rms 50Hz, 1 Min.
 Durability: 600 cycles Min.
 Operation Temperature: -40°C~+70°C

Order Information


RHTLY17-6P6C - X- 1 -XX

Contacts: 6P6C
 Panel Code: _____
 W-With Panel
 W/0-Without Panel
 Plating Code: _____
 01-Fu' Gold Plating
 02-3u' Gold Plating
 03-6u' Gold Plating
 04-15u' Gold Plating
 05-30u' Gold Plating

RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5

CHK'D BY FENG
 APPR BY ZHAN

RJ12-6P6C Modular jacks
 THIRD ANGLE PROJECTION

 RHTLY17-6P6C-X-1-XX