



Material:

Housing: Engineering Thermoplastic

Flammability Rating: UL94V-0

Contacts: Phosphor Bronze

Plating: Gold Plating Over Nickel in Contact.

Tin Plating Over Nickel in Solder Area.

Electrical:

Voltage Rating: 125VAC

Current Rating: 1.5A

Contact Resistance: 40mΩ Max.

Insulation Resistance: 1000MΩ Min. @500VDC

Dielectric Strength: 1000VAC Rms 60Hz, 1 Min.

Durability: 750 cycles Min.

Operation Temperature: -20°C ~ +75°C

Order Information

RHTLY52-8P8C-S-1-XX

Contacts: 8P8C

Color Code:  
1-Block

Plating Code:

01-Fu" Gold Plating

02-3u" Gold Plating

03-6u" Gold Plating

04-15u" Gold Plating

05-30u" Gold Plating

 NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4			SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG	
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	

RJ45-8P8C Vertical Modular jacks

THIRD ANGLE PROJECTION



RHTLY52-8P8C-S-1-XX