



H
3.8
4.8
7.0
8.5

ELECTRICAL

- 1.Rating:50mA 12VDC
- 2.Contact Resistance :50mΩ max(Initial)
- 3.Insulation Resistance:100MΩ(minDC 250V)
- 4.Dielectric Strength:AC250V(50/60Hz For 1minute)
- 5.Electrically Life:100000 Cycles
- 6.Environment Temperature:-20℃~+70℃
- 7.Operating Force: 180/250(±30gf)
- 8.Seal Temperature:260℃~280℃



PCB LAYOUT

ORDER INFORMATION

RHTGYS4501-4.3-180-B

Series No _____

Height: 4.3mm/4.5mm/5.0mm/
7.0mm/7.5mm/8.0mm/8.5mm/
9.0mm/10.0mm/11.0mm/12.0mm
/13.0mm15.0mm/18.0mm

Operating Force :180~250gf _____


Packing: B=Bulk T=Tape _____

RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4			SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG	
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	

4.5x4.5mm Tact Switch Series

THIRD ANGLE PROJECTION



RHTGYS4501