



**SPECIFICATIONS**  
 Rating: 3A 125VAC; 1A 250VAC  
 Contact Resistance: 20MΩ max  
 Insulation Resistance: 500V DC 1000MΩ Min  
 Dielectric Strength: 1000V AC 1 Minute  
 Operating Temperature: -25°C~+65°C  
 Electrical Life: ≥20,000 Cycles

**ORDER INFORMATION**  
 RHTGYRLS-1 02-A 4 X X

Sub-miniature Rocker Switch Series  
 POLES 1=Single Pole  
 2=Double Pole  
 CIRCUIT: 01=ON-OFF 02=ON-ON  
 03=ON-OFF-ON  
 Handle Type: A=Standard C=Short  
 Terminal Type: 1=Solder Terminal  
 2=Pc Terminal 3=Pc-H Terminal  
 4=Pc-V Terminal  
 Handle Cap Type: R=Red B=Black  
 W=White Y=Yellow G=Green BL=Blue  
 BRACKET: T=With Bracket  
 None=Without Bracket

G	NINGBO RHT ELECTRONIC CO.,LTD			UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN	Sub-Miniature Rocker Switch Series	
				0~3	3~18	18~50	50~120		
				±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	THIRD ANGLE PROJECTION 
1	2	3	4	5	6	7	8	9	