



MATERIAL

- 1.Housing: Nylon 66
- 2.Rocker: PC & PA66
- 3.Contacts: Silver Alloy
- 4.Terminal: Brass Silver Plated
- 5.Lamp: Neon Lamp, Tungsten Lamp
- 6.Spring: SWP, SUS
- 7.Movable Arm: Brass Silver Plated



ELECTRICAL

- 1.Electrical Rating: 16(4)A 250VAC T85
16(4)A 250VAC T125/55 1E4
16A 125V/8A 250AC
(H)Rating: 16(8)A 250VAC T85/55 1E4
- 2.Mechanical Life: Over 30000 Cycles
- 3.Electrical Life: Over 10000 Cycles
- 4.Contact Resistance: $\lt; 20m\Omega$
- 5.Insulation Resistance: >1000M Ω
- 6.High Voltage Resistance: >1500V 1 min
- 7.Ambient Temperature: Terminal Side -20°C~+85°C;
Actuating Side -20°C~+55°C
- 8.Storage Temperature: -30°C~+80°C Max
- 9.Atmospheric Humidity: Max 85%
- 10.Actuating Force: 4~8N (Depends On Different Witch Function)
- 11.Flammability: UL94V-2
- 12.Temperature Rise At The Terminal: Max 30°C (UL1054)
- 13.Solder Ability Of Terminal: Max 350°C 3S

ORDER INFORMATION

RHTGY07-21/N-C-2 RE/BK -P1 -S(2)

Series No

<p>Function</p> <p>21/NON-OFF 4P W/Lamp</p> <p>21/ON-OFF 4P</p> <p>22/ON-OFF 6P</p> <p>23/ON-OFF-ON 6P</p> <p>11/ON-OFF 2P</p> <p>12/ON-ON 3P</p>	<p>Cap Type</p> <p>A: Fast</p> <p>C: Soft Line</p> <p>P: W/PVC-Cap</p> <p>7: </p> <p>6: </p>	<p>Cap Printing</p> <p>0: None</p> <p>1: </p> <p>2: </p> <p>3: </p> <p>4: </p> <p>5: </p> <p>8: </p>	<p>Color Cap/Housing</p> <p>BK: Black</p> <p>WT: White</p> <p>RE: Red</p> <p>OR: Orange</p> <p>GR: Green</p> <p>BL: Blue</p> <p>GE: Grey</p>	<p>Terminal</p>	<p>Panel Hole Size</p> <p>S: 28*22</p> <p>G: 28.5*22</p>	<p>Voltage</p> <p>1: 110VAC</p> <p>2: 220VAC</p> <p>3: 12VDC</p> <p>4: 24VDC</p>
---	--	--	--	-----------------	--	--

NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4	SCALE: ---	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5
CHK'D BY FENG		APPR BY ZHAN	

Rocker Switch Series

THIRD ANGLE PROJECTION

RHTGY07