


Note:

- 1: V.S.W.R:1.5(0~3G), Max.
- 2: Wire surface shall have no dirt, broken.
- 3: Connector surface with coating, oxidation phenomenon.
- 4: Connector pins and insulator are in the same plane

Order Information

RHTAYFCA03-RG174-L300



6	Nut	T1.8mm Nut,1/436UNS-2A	PCS	1
5	Washers	T0.4mm Washers	PCS	1
4	Connector	SMA Jack,Female Straight ,for RG174,with CAP(Red)	PCS	1
3	RF Cable	RG174 Cable, Black,OD2.7mm	mm	L
2	Heat-Shrink Tube	ø2.5mm Heat-Shrink Tube,Block,L15mm	PCS	2
1	Connector	SMA Plug,Male Straight,for RG174 or RG316	PCS	1
No.	Name	Description	UNITS	Q'ty

	NINGBO RHT ELECTRONIC CO.,LTD				UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN	SMA Female to SMA Male Cable		
					0~3	3~18	18~50	50~120	CHK'D BY FENG	THIRD ANGLE PROJECTION 	RHTAYFCA03-XXXX
					±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN		
1	2	3	4	5	6	7	8	9			