

**Material&SPEC**

- 1.Shell Material:PPD,PA66 UL94V-0
- 2.Insulation Materials:PPS, High Temperature 260°C
- 3.Contact:Brass,Gold-Plated
- 4.Insulation Resistance:≥2000MΩ
- 5.Number Of Poles:2~9 Poles
- 6.Coupling:Threaded
- 7.Termination:Solder
- 8.Cable Outer Diameter:Not-4~6.5mm;G-5~8mm
- 9.IP Rating:IP68
- 10.Durability:500 Mating Cycles
- 11.Temperature Range:-25°C~+80°C

**ORDER INFORMATION:**

RHTOY13 A4-XX

IP68 Connector Type  
 Female Plug For Cable  
 Number Of Poles, 2~9 Poles

**Solder Contact Arrangement And Spec**


Number Of Contact	2	3	4	5	6	7	9
Male Contact Face View							
Rated Current (A)	13A	13A	5A	5A	5A	5A	3A
Contact Diameter	∅1.6x2	∅1.6x3	∅1.0x4	∅1.0x5	∅1.0x6	∅1.0x7	∅0.7x9
Rated Voltage(AC.V)	250V	250V	200V	180V	125V	125V	125V
Test Voltage(AC.V)1 Min	1500V	1500V	1500V	1000V	1000V	1000V	1000V
Contact Resistance mΩ	2	2	5	5	5	5	10
Wire Size Solder mm <sup>2</sup> /AWG	≤2/14	≤2/14	≤0.785/18	≤0.785/18	≤0.785/18	≤0.785/18	≤0.785/18

Match Connector	
RHTOY13A1	

**RHTECP** NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5

CHK'D BY FENG
APPR BY ZHAN



IP68 W13 CONN,Female Plug For Cable,Solder

RHTOY13A4-XX